

Coding P

Coding R

Assembly / profile machining

1

5

n	Bundle Pieces	b	d ₁	d ₂	l ₁ ≈	l ₂	l ₃	m	A/F	Tightening torque in Nm
10	4	10	6,8	10	46	10,3	20	22,5	3	6

2

Type

S Symmetrical mounting stud

3

Coding

P Parallel T-nut
R Right-angle T-nut

Specification	4
Steel	SZ
Zinc plated, blue passivated	
RoHS	

Quick release connectors GN 25b fasten aluminum profiles together at right angles. Only one profile has to be machined. The connection can be freely positioned and slid along the slot. The internal hex used for clamping is situated for especially easy access. If panels are used, they must be suitably pocketed depending on the type, coding and installation orientation. Quick release connectors of type S are used when the slot is to be closed by a cover profile. Quick release connectors are supplied in bundles. The table shows the quantity included in each bundle.

see also...	Page
GN 10b Aluminum Profiles (Profile Type Light)	QVX
GN 10b Aluminum Profiles (Profile Type Heavy)	QVX

Technical Information	
Assembly Instructions / Profile Machining	QVX

How to order	1 n
	2 Type
	3 Coding
	4 Material / Finish
	5 Bundle
GN 25b-10-S-R-SZ-4	

3.7 Connecting, Assembling with Clamping and Connecting Elements

1