



**elesa**  
Original design T.440

## 2 Type

- A Without dipstick
- B With dipstick

1

| <b>d<sub>1</sub></b> | <b>d<sub>2</sub></b> | <b>l<sub>1</sub></b> | <b>l<sub>2</sub></b> | <b>l<sub>3</sub></b> |
|----------------------|----------------------|----------------------|----------------------|----------------------|
| G 1/4                | 20,5                 | 9                    | 19                   | 192                  |
| G 5/8                | 25                   | 9                    | 21                   | 192                  |
| G 1/2                | 28                   | 11                   | 25                   | 189                  |
| G 3/4                | 34                   | 12                   | 27                   | 188                  |
| G 1                  | 42                   | 13                   | 29                   | 188                  |
| G 1 1/4              | 52                   | 13                   | 32                   | 185                  |
| G 1 1/2              | 57                   | 13                   | 35                   | 185                  |

## Specification

- Plastic (Polyamide PA)
  - Temperature resistant up to 100 °C
  - Black, matte finish
- Seal
  - Rubber NBR (Perbunan®)
- Dipstick
  - Steel, phosphated
- Elastomer Characteristics → Page 2158
- Plastic Characteristics → Page 2158
- RoHS

## Information

From thread size G 1/2 upwards, the seal of the plugs GN 548.1 is embedded in a radial undercut. For this reason the seal cannot be extruded when tightening the plug.

MAX-MIN lines can easily be marked on the two flat sides of the dipstick (see GN 109 → Page 2083).

see also...

- Threaded Plugs GN 441 / GN 442 (with Wing Knob) → Page 1599

## On request

- Level Markings / Special Lengths GN 109
  - Page 2083

### How to order

**GN 548.1 - G 1/2 - B**



1 d<sub>1</sub>

2 Type