



# Original design EBP.SAN









**B** Mounting from the operator's side



V	Ą								
I <sub>1</sub>	d <sub>1</sub>	d <sub>2</sub>	h <sub>1</sub>	h <sub>2</sub>	I <sub>2</sub>	I <sub>3</sub> min.	s	A/F	t
117 ±0,5	8,5	26	39	18	143	91	8,5	13	8,5
179 ±1	8,5	29	51	19	208	150	9,5	13	16

see also...

## Specification

#### Handle

Plastic, Polyamide (PA)

· Glass fiber reinforced

• Operating temperature -30 °C to +130 °C

· Black-gray, RAL 7021, matte finish

· White, RAL 9016, matte finish

### SGA ○ WSA

4

#### Cover cap

Plastic, Polyamide (PA)

• Black-gray (for SGA)

· White (for WSA)

**RoHS** 

Cabinet U-handles GN 628.1 are manufactured from an antimicrobial plastic. Adding a silver-based substance has created a natural active agent that helps to prevent the growth of bacteria. Even after repeated cleaning with soap or solvent, the antimicrobial effect of this additive will not diminish. Sterilising at temperatures below 130 °C will also have no effect on the antimicrobial property.

With these properties, the handles are the perfect choice for use in medical engineering, in the food and the pharmaceutical industry, and in general wherever hygiene is of great importance.

GN 628 Cabinet U-Handles (Mounting from the Operator's Side or Back)				
Technical Information				
Product Family Sanline	QVX			
Product Family Ergostyle®	QVX			
Strength Properties	QVX			
Plastic Characteristics	QVX			

GN 628.2 Distance Bushings	QV>	
How to order	1	I <sub>1</sub>
	2	d <sub>1</sub>
1 2 3 4	3	Туре
GN 628.1-117-8,5-B-SG/	4	Color

Page