


Application example



1 2

| m ₁ | h ₁ | b | d ₁ | d ₂ | d ₃ | d ₄ | h ₂ | m ₂ | Length l | For toggle clamps | | |
|----------------|----------------|------|----------------|----------------|----------------|----------------|----------------|----------------|----------|--|--|--------|
| | | | | | | | | | | GN 810 GN 810.1 GN 810.3 GN 810.4 | GN 820 GN 820.1 GN 820.2 GN 820.3 GN 820.4 | GN 860 |
| 82 | 16 | 19,5 | 6,2 | M 6 | 9,2 | 12 | 37 | 22 | 91 | 130 | 130 | 125 |
| 100 | 18 | 26 | 8 | M 8 | 12 | 16 | 43 | 27 | 112 | 230 | 230 | 200 |

Specification

- Steel
- Zinc plated, blue passivated
- RoHS

3

ST

Information

Clamping arm extenders GN 801.2 are used together with toggle clamps with "forked clamping arm" to clamp something simultaneously at two points in parallel, such as with clamping screws. These are mounted to the clamping arm and affixed in the desired position along the slot.

The side position of the clamping screws is adjusted via joints that enable any positioning of the spindle assemblies. A symmetrical arrangement/setting encourages a balanced clamping result.

All parts are supplied in a non-assembled set. Four flanged washers are included for fastening the clamping screw.

see also...

- Clamping Arm Extenders GN 801.1 (Rigid) → Page 816
- Clamping Arm Extenders GN 809.1 → Page 819
- Clamping Screws GN 804 → Page 810
- Clamping Screws GN 807 → Page 811

How to order

GN801.2-82-16-ST

| | |
|---|----------------|
| 1 | m ₁ |
| 2 | h ₁ |
| 3 | Material |

